
Nimble204

Portable Ceiling Lifter



Nimble240

The Nimble 204 portable system is designed for clinicians to transfer a patient lift from room to room. It is the smallest and lightest portable patient lift in the world today.



PRODUCT
CODE:
HA1020

Safety Features:

- Emergency stop
- Emergency lowering device: Independent circuit
- Manual lowering
- Upper limit detection
- Lower limit detection
- Slack tape sensor
- Free fall brake (over speed governor)
- Low battery and dead battery alarms
- Soft start and stop
- Overload protection

Product Features:

- Wired hand control
- Light weight and portable
- LED indicators
- Infection control
- Durable and strong
- Easy to service
- Magnetic hand control docking

Specifications:

Maximum Lifting Speed	No load: 1.7 inches/second 150 lbs/68 kg: 1.3 inches/second 450 lbs/204 kg: 1.0 inch/second
Unit Weight	6 lbs (2.72 kg)
Safe Working Load (SWL)	450 lbs (204 kgs)
Dimensions	Length: 19.4" (49.27 cm) Height: 5.2" (13.20 cm) Depth of Lift: 3.7" (9.398 cm) Strap Length: 74" (187.96 cm)
Number of Lifts per Charge (Duty: 10/90):	78 with 150 lbs (25% of strap at midrange) 46 with 450 lbs (25% of strap at midrange) Charging time: 2-4 Hours
Lift Case	Flame retardant ABS IP23 Lift - protected from fingers and water Spray less 60 degrees from vertical
Batteries	High Capacity, Long Lasting NiMH 1 x 24V (1.6Ah)
Battery Charger	Input: 100-240VAC Output: 36VDC, 40 Watt, 1.0A
Hand Control	IPX4 Hand Control – protects from splashing water, no matter the direction
Approvals	CAN/CSA-C22.2 No 60601-1:08 CAN/CSA-Z10535.1:15
Expected Service Life	22,500 cycles or 10 years. It is recommended that the lift be replaced after this time. The expected life of slings, batteries fuses, straps and cord is dependent upon proper maintenance.
Warranty	24 Months

Nimble Free Standing Gantry

The Nimble Gantry is a portable freestanding lift stand which, in combination with a rail and a ceiling lift motor, functions as a stationary lift system. The gantry is an ideal solution for occasional lifting needs in a specific location, or where it is not possible to install a permanent rail system on the ceiling.



Features:

- Sturdy and stable construction
- Made of aluminium
- Easy to assemble and disassemble
- Easy to move and store
- For use with both fixed and portable ceiling lift motors
- Weight capacity 204 kg
- Set up in 5 minutes
- Width: 2.34 m
- Height 2.11 m

Through our innovative, quality products, exceptional service and ingrained knowledge and expertise of the healthcare industry, Highgate Healthcare has been raising the standard of living in aged care, hospital, disability and rehabilitation facilities in Australia for over 30 years.



Highgate Healthcare

1300 350 350

2 Selgar Avenue Tonsley SA 5042

highgatehealthcare.com.au